





ROCKER SWITCHES


1 GANG




2 GANG



3 GANG



4 GANG





Rocker Switch

Standards, Approvals & Directives

Conforms to BS EN 60669 - 1: 1999 when assembled to appropriate plate and grid and installed correctly.

ASTA Certificate No: 16240

Nemco Certificate No: C15/47987

Description:

Rocker switches are manufactured from brass, aluminium or plastic and finished to complement or match the cover plates. Switches are available as 2-way, intermediate, momentary and 2-way-and-off.

Features:

- Solid Brass/Aluminium rockers
- Two way switches can be wired as one or two way
- All products clearly printed with BS No's, ratings, etc
- 3mm switch contact gap
- Positive switch action

Finishes:

Rocker switch available with our complete range of plate finishes: Unlacquered Brass, Antique Bronze, Stainless Steel, Polished Nickel, Verdigris and Invisible. Steel, Polished Nickel, Verdigris and Invisible.

Technical Specification	
Voltage Rating:	250V AC, 50Hz
Current Rating:	20AX
Terminal Capacities:	4 x 1mm ²
	4 x 1.5mm ²
	3 x 2.5mm ²
	2 x 4mm ²
	1 x 6mm ²
Operating Temperature:	-5°C to + 40°C
IP Rating:	IP2XD
Max. Installation Altitude:	2000 Meters
No. of Operations:	10,000 (20AX Rating)
	40,000 (6AX Rating)